

SUPERCHEM 1611

Extreme Pressure Grease, Calcium sulfonate complex, Multi-purpose



Product Description

SUPERCHEM 1611 is a calcium sulfonate complex grease designed for high temperature bearing applications. It's outstanding stability and water wash-out resistance make it an ideal choice for applications in wet, hot and corrosive environments.

Features

- Color: Dark Red
- Dropping Point: >300°C (NLGI 00 ~ 4)
- Shear Stability: 10,000 times +2%; 100,000 times +3%
- Water Washout: 0 ~ 1%*
- Continue working Temp.: -40 ~ 200°C
- Copper Corrosion Test (GB/T 7326): Pass
- Four Ball Weld Test (ASTM D2596): ≥500KG (1100 Lbs)
- Four Ball Wear Test (ASTM D2266): <0.5mm

* Lab results for individual production lots tested; some variability will occur

SUPERCHEM 1615

High Temp. Extreme Pressure Grease, Calcium sulfonate complex, Multi-purpose



Product Description

SUPERCHEM 1615 has excellent water washout resistance and outstanding pressure capabilities. Superchem 1615 is a high performance, corrosion inhibiting Calcium sulfonate grease suitable for centralised lubrication systems.

Features

- Color: Blue
- Dropping Point: >320°C (NLGI 1 ~ 4)
- Shear Stability: 10,000 times +2%; 100,000 times +3%
- Water Washout: 0 ~ 1%*
- Continue working Temp.: -40 ~ 200°C
- Copper Corrosion Test (GB/T 7326): Pass
- Four Ball Weld Test (ASTM D2596): ≥500KG (1100 Lbs)
- Four Ball Wear Test (ASTM D2266): <0.5mm

* Lab results for individual production lots tested; some variability will occur



SUPERCHEM® | A Brand under AIGI Environmental Inc.

81 Suyuan Avenue, Jiangning District, Nanjing 211100, PR China

www.aigienviroental.com

